



# UPS Line Interactive BL2

The UPS Accupower is designed to cover all your needs.

## SPECIFICATIONS BL2 1000 / 1400 / 2000 VA

- ✓ Led Panel
- ✓ Easy installation
- ✓ Compact design
- ✓ 2 IEC outputs
- ✓ 2 shucko outputs
- ✓ Easy battery replacement
- ✓ Sound alarm
- ✓ Auto restart with AC recovery
- ✓ Auto turn on when plug-in
- ✓ Microprocessor control guarantees high reliability
- ✓ With modem/phone line surge protection
- ✓ Provides boost and buck AVR to stabilize input voltage
- ✓ Provides lightning, surge, overload, and short-circuit protections
- ✓ Built-in RS-232 communication port with free download software from the Internet



MODEL		BL2 1000	BL2 1400	BL2 2000
<b>POWER</b>	VA/W	1000 VA / 600W	1400VA / 840W	2000VA / 1200W
<b>INPUT</b>	Voltage / Voltage Range	220-230-240VAC / 166V – 290V		
	Frequency	50Hz or 60Hz		
<b>OUTPUT</b>	Voltage / Voltage Regulation (Battery Mode)	220-230-240 VAC / ±10%	220-230-240 VAC / ±5% at load <50%	
	Frequency / Frequency Regulation (Battery Mode)	50Hz or 60Hz / ±1 Hz		
	Output Waveform	Modified Sinewave		
<b>BATTERIES</b>	Battery Type	Lead acid 12V/7Ah x 2pc or equal	Lead acid 12V/9Ah x 2pc or equal	
	Backup Time (with a PC load)	23 min.	25 min.	26 min.
	Recharge Time	6 hours to 90% after complete discharge		
<b>TRANSFER TIME</b>		4-8ms		
<b>INDICATOR</b>	AC Mode	Green LED lighting Indicators 2-5 light progressively depending on the attached load		
	Backup Mode	Green LED flashing Indicators 2-5 light progressively depending on the battery charge		
	Alarm	Red ED lighting		
<b>SOUND ALARM</b>	Backup Mode	Sounding every 10 sec		
	Low battery	Sounding every 1 sec		
	Overload	Sounding every 0.5 sec		
	Alarm	Continuous		
<b>PROTECTION</b>	Full Protection	Under/Over voltage, peak voltage, short circuit, and AC/DC fuse protection		
<b>DIMANSIONS</b>	(mm), D x W x H	405 x 205 x 145		
<b>WEIGHT</b>	Net Weight	9.6kgs	9,7kgs	9,8kgs
<b>ENVIRONMENT</b>	Operating Environment	0- 40°C on full load, 0-90 % relative humidity (non-condensing)		
	Noise Level	Less than 45dB		
<b>INTERFACE</b>	Smart RS-232	Windows family, Linux, Sun Solaris, IBM AIX, HP-UX , Compaq True64, UnixWare, FreeBSD, and MAC		

Specifications are subject to change without notice.

